

SINCE 1978



LEADING LIGHT

Product Datasheet

vkleadinglight.gr

Sora

VK/04696/PE/D/W/W




White. 3000K. 10W. 823lm. AC220-240V. 36°. LED Bridgelux COB. Driver KGP. Ceiling/pendant. -20°C → 45°C. 50.000hrs. Clicks 20.000. Dimmable Yes, triac. CRI>90. Glass+Aluminum. IP20

IP20



Dimensions



Gallery





Downloads




VK Leading Light

Since 1978

Technical Specifications	
Kelvin	3000K
Power	10W
Voltage	AC220-240V
Fitting	Pendant
Type	Light
Safety class	
Light source	Bridgelux COB
IP Rating	IP20
CRI	CRI>90
Dimmable	 TRIAC
Lifetime	50.000hrs
Clicks	20,000
Driver	KGP
Cable Length	300cm (max)
Working temperature	-20°C-45°C
PAGE	118 New Products 2026
NICKNAME	Sora

Physical Specifications	
Family	Sora
Color	White
Material	Glass + Aluminum
Width	ø20cm
Length	ø20cm
Height	25cm + 11cm (+300cm of cable)
Net weight of product (kg)	1.50kg
Gross weight with inner box (kg)	1.86kg
Width (inner box)	25.5cm
Length (inner box)	36.5cm
Height (inner box)	10.8cm

Illumination Data	
Lumen	823lm
Beam angle	36°
Lighting direction	

Packing Info	
Pcs/carton	6pcs

Certification & Warranty	
Guarantee	2 years