

SINCE 1978



LEADING LIGHT

# Product Datasheet

[vkleadinglight.gr](http://vkleadinglight.gr)

Run

## VK/02288/RB/W




Rust brown. With 2 sockets type F (schuko) Max. 2x2200W. 3000K. 355lm. 5W. AC220V-240V. 52°. 30.000hrs. Dimmable No. -20°C→ 45°C. Outdoor ground. Used as socket & LED light. CRI>80. Die-casting aluminum+Silicone rubber gasket. IP54

IP54



### Dimensions



### Gallery





### Downloads




**VK Leading Light**

Since 1978

Technical Specifications	
Kelvin	3000K
Power	5W
Voltage	AC220-240V
Fitting	Outdoor ground
Type	Socket & Light
Safety class	
IP Rating	<b>IP54</b>
CRI	CRI>80
Dimmable	
Lifetime	30.000hrs
Clicks	25,000
Working temperature	-20°C-45°C
PAGE	360 New Products 2026
NICKNAME	Run

Physical Specifications	
Family	Run
Color	Rust brown
Material	Die-casting aluminum+Silicone rubber gasket
Width	9.2cm
Length	11cm
Height	42.6cm
Net weight of product (kg)	2.05kg
Gross weight with inner box (kg)	2.3kg
Width (inner box)	11.5cm
Length (inner box)	13.5cm
Height (inner box)	52cm

## Illumination Data

Lumen	355lm
Beam angle	52°
Lighting direction	


## Packing Info

Pcs/carton	4pcs
------------	------

## Certification &amp; Warranty

Guarantee	3 years
-----------	---------

## Energy Label



VK LEADING LIGHT  
VK/02288/RB/W

A	▶
B	▶
C	▶
D	▶
E	▶
F	▶
G	◀

6 kWh/1000h



2019/2015