

SINCE 1978



LEADING LIGHT

Product Datasheet

vkleadinglight.gr


VK/04611/W-CB/W

Blin

Recessed dark downlight led. 3000K. 1.860lm. 15W. CRI>90, IP20, Titanium-White-Chrome-black



IP20    

Dimensions	Gallery	Downloads
	 	  

Technical Specifications	
Kelvin	3000K
Power	15W
Voltage	220-240V
Fitting	Recessed dark ceiling
Type	Downlight LED
Safety class	
Light source	Bridgelux
IP Rating	IP20
CRI	CRI>90
Dimmable	
Lifetime	50.000hrs
Working temperature	<45°C
PAGE	192 Technical 2024
NICKNAME	Blin

Physical Specifications	
Recessed ceiling	Yes
Color	Titanium-white-chrome-black
Material	Aluminium+PMMA lens
Width	ø12.5cm
Length	ø12.5cm
Height	11.4cm
Net weight of product (kg)	0.41
Gross weight with inner box (kg)	0.53
Gross weight with master box (kg)	7
Cut out	ø9cm
Width (inner box)	18.5cm
Length (inner box)	18.5cm
Height (inner box)	12.5cm

Illumination Data	
Lumen	1.860lm
Beam angle	36°
Lighting direction	
Dark light	Yes

Packing Info	
Pcs/carton	12pcs

Certification & Warranty	
Guarantee	5 years

Energy Label



VK LEADING LIGHT

VK/04611/W-CB/W

A

B

C

D

E

F

G

15

kWh/1000h



2019/2015